WATER-SUPPLY DIVISION.

Dated 4th February 1918.

Notice is hereby given that sealed tenders will be received at the office of the Executive Engineer, Water-Supply Division up to 12 noon of 1st May 1918, for the supply of 2,000 tons of jungle fuel and 3,000 tons of cassurina fuel for Soldevanhalli Pumping Station for the year 1918-19. The supply should be completed by the end of March 1919.

Tenders should be submitted on printed forms which may be obtained from the Executive Engineer. The tenders should be accompanied by a statement in the form given below, showing the rates at which the different items specified will be executed.

Description of work.	Unit of work	Rate per unit
Supply of jungle fuel	Ton.	
Supply of Cassurina fuel	Ton	

Each tender must be accompanied by a deposit of Rs. 2,000 in Government Promissory Notes, as earnest money and be superscribed "Tender for the supply of Cassurina and Jungle fuel to Soldevanhalli Pumping Station," in default of which tenders will be rejected.

The final acceptance of the tender will rest with the Chief Engineer, who does not bind himself to accept the lowest or any tender or to assign any reason whatever for the rejection of any tender.

Within eight days of the acceptance of the tender, the successful competitor will be required to execute the usual contract bond; in default of which, his tender will be considered cancelled, and his earnest money will be forfeited.

The name of the successful competitor, whose tender has been accepted, will be posted on the notice board in the Executive Engineer's office in due course. No enquiries regarding the acceptance or rejection of a tender will receive any reply.

On acceptance of one of the tenders, the earnest money on rejected tenders will be returned.

Specifications for jungle and cassurina fuel are herewith attached.

The contractor whose tender is accepted should begin the collection from 1st July 1918 or fifteen days from date of intimation of the acceptance of his tender from this office if the same is not received within the 15th of June 1918.

During the first month at least 400 tons of fuel should be supplied.

The monthly supply for the remaining period shall not be less than 600 tons of fuel subject to the maximum limit of 4,600 tons.

Dated 4th February 1918.

Notice is hereby given that sealed tenders will be received at the office of the Executive Engineer, Water-Supply Division, up to 12 noon of 1st May 1918, for the supply of 3,000 tons of jungle fuel and 2,000 tons of cassurina fuel for Bethamangala Pumping Station for the year 1918-19. The supply should be completed by the end of March 1919.

Tenders should be submitted on printed forms which may be obtained from the Executive Engineer. The tenders should be accompanied by a statement in the form given below, showing the rates at which the different items specified will be executed.

Description of work	Unit of work	Rate per unit
Supply of jungle fuel	Ton.	
Supply of cassurina fuel	Ton.	

Each tender must be accompanied by a deposit of Rs. 2,000 in Government Promissory Notes, as earnest money, and be superscribed " Tender for the supply of Cassurina and Jungle fuel to Bethamangala Pumping Station," in default of which tenders will be rejected.

The final acceptance of any tender will rest with the Chief Engineer, who does not bind himself to accept the lowest or any tender or to assign any reason whatever for the rejection of any tender.

Within eight days of the acceptance of the tender, the successful competitor will be required to execute the usual contract bond; in default of which, his tender will be considered cancelled, and his earnest money will be forfeited.

The name of the successful competitor, whose tender has been accepted will be posted on the notice board in the Executive Engineer's office in due course. No enquiries regarding the acceptance or rejection of a tender will receive any reply.

On acceptance of one of the tenders, the earnest money on rejected tenders will be returned.

Specifications for jungle and cassurina fuel are herewith attached.

The contractor whose tender is accepted should begin the collection from 1st July 1918, or fifteen days from date of intimation of the acceptance of his tender from this office if the same is not received within the 15th of June 1918.

During the first month at least 300 tons of jungle and 100 tons of cassurina should be supplied.

The monthly collection of the balance should not be less than 350 tons of jungle and 250 tons of cassurina subject to the maximum limit of 3,700 tons of the former and 900 tons of the latter.

Notice dated 4th February 1918.

Notice is hereby given that sealed tenders will be received by the undersigned up to 12 noon of the 1st May 1918, for the supply of the undermentioned article required for the use of this Division.

2. An approximate estimate of quantities required is given against each item.

3. Each tender much be accompanied by a deposit of Rs. 300 as earnest money, and superscribed "Tender for the supply of charcoal to pumping station at Harihar."

4. The final acceptance of the tender will rest with the undersigned, who does not bind himself to accept the lowest or any tender or assign any reason whatever for the rejection of any tender.

5. The name of the successful competitor whose tender has been accepted, will be posted on the Notice Board in the undersigned's office in the usual course, and no enquiries regarding the acceptance of a tender will receive attention.

6. The contractor whose tender is accepted should begin the collection from 1st July 1918, or fifteen days from date of intimation of the acceptance of his tender from this office, if the same is not received within the 15th June 1918.

7. During the first month at least 20 tons should be supplied.

8. The monthly collection of the balance should not be less than 15 tons subject to the maximum limit of 130 tons.

9. The rate tendered for shall include cost of delivery at Harihar Railway Station and not Ex-Godown.

10. If any of the above terms are not fulfilled while execution of the contract, the earnest money shall be forfeited to Government and the contract cancelled.

Specification for Charcoal.

The wood to be used for burning charcoal must be hard such as Jali, Thopala, devadari, hunse, chigari, hiddarne or some other approved variety.

The charcoal prepared out of soft wood and containing small pieces are liable to be rejected or paid for at lower rate at the discretion of the officer in charge.

No.	Particulars	Quantity required.
1	Charcoal for working gas engine at Harihar ...	150 tons.

SPECIFICATION.

The wood to be jungle fuel.

The maximum and minimum dimensions which will be accepted are given below :—

Length.		*Thickness.*	
Maximum.	Minimum.	Maximum.	Minimum.
24"	18"	7"	3"

The billets are to be sawn and not chopped. Billets of over 7 inches in diameter to be split.

The wood to be stacked by the contractor in the portion approved of by the Executive Engineer or his representative.

Stacks must be of rectangular shape, the sides being vertical and straight and the top level. The wood must be laid evenly straight and close, the pieces composing the walls must be laid at right angles to the direction of such walls, having first been sawn to an uniform length as above.

The interior of the stacks must be packed as closely as possible, the pieces being regularly laid with their lengths all in the one direction which leave no vacant space.

The stacks to be built of such dimensions that the cubical contents of each is a multiple of 75 cubic feet.

$$15' \times 10' \times 5' = 750 \text{ cubic feet} = 10 \text{ tons.}$$

Seventy-five cubic feet of closely packed wood will be accepted as equivalent to a ton.

The Executive Engineer or his representatives will inspect the wood as it is being stacked and shall have power to reject any pieces that are hollow, rotten or otherwise unsuitable for fuel for boilers; he will also satisfy himself that the pieces are in accordance with the dimensions specified above and that the stacks are built as required. He shall have power to reject any stacks that do not in all respects comply with the terms of the specification.

The wood must be at the risk of the contractor until it is stacked, measured and accepted by the Executive Engineer or his representatives.

When stacks are taken over, the contractor or his representative must be present during the measurement and must sign the record of measurement in token of his agreement to the correctness thereof.

Soft wood unsuitable for steaming purposes will not be accepted.

Jali, thopyala, devadari, hunse, chigari, heddarne, gorve and other equally hard wood than those specified above and which the contractor would like to supply, may be supplied after he has got the previous sanction of the Executive Engineer or his representatives. A cart-load of the proposed fuel to be brought in first when the same will be tested and if suitable the contractor will be given permission in writing to such wood also in addition to the list of wood already approved of.

SPECIFICATION FOR CASUARINA FUEL.

1. The wood to be solely casuarina and to be in straight lengths. The maximum and minimum dimensions which will be accepted are given below:—

	Length.		Thickness.	
	Maximum.	Minimum.	Maximum.	Minimum.
Running wood	24"	18"	8"	3"

The billets are to be sawn to lengths, not chopped.

The wood to be stacked by the contractor in the portion approved by the Executive Engineer or his representatives.

Stacks must be of rectangular shape, the sides being vertical and straight and the tops level; the wood must be laid evenly straight and close; the pieces composing the walls must be laid at right angle to the direction of such walls, having first been sawn to an uniform length as above; the interior of the stacks must be packed as closely as possible, the pieces being regularly laid with their lengths all in the one direction which leave no vacant space.

The stacks to be built of such dimensions that the cubical measurements of each is a multiple of 68 cubic feet.

17 feet by 8 feet by 5 feet = 680 cubic feet = 10 tons.

Sixty-eight feet of closely stacked wood will be accepted as equivalent to one ton.

The Executive Engineer or his representatives will inspect the wood as it is being stacked and shall have power to reject any pieces that are hollow, rotten, crooked or otherwise unsuitable for fuel for engines; he will also satisfy himself that the pieces are in accordance with the dimensions specified above and that the stacks are built as required; he shall also have power to reject any stacks which do not, in all respects, comply with the terms of this specification.

The wood must be at the risk of the contractor until it is stacked, approved, measured and accepted by the Executive Engineer or his representatives.

When stacks are taken over, the contractor or his representative must be present during the measurement and must sign the record of measurement made by the Executive Engineer or his representatives in token of his agreement to the corrections thereof.

Notification dated 7th February 1918.

Notice is hereby given that sealed tenders will be received by the undersigned up to 12 noon of 1st May 1918, for the supply of 730 kerosene oil tins of superior quality with or without tins required for the use of Harihar Pumping Station during the official year 1st July 1918 to 30th June 1919.

2. Tenders should be submitted in printed forms which may be obtained from the undersigned's office.

3. Each tender must be accompanied by a deposit of Rs. 200 as earnest money, and be superscribed "Tender for the supply of kerosene oil for Harihar Pumping Station," in default of which tenders will be rejected.

4. The final acceptance of any tender will rest with the Executive Engineer, Water-Supply Division, who does not bind himself to accept the lowest or any tender or assign any reason whatsoever for the rejection of any tender.

5. The rate tendered should include the cost of delivery at Harihar Pumping Station and not at godown.

6. The supply should be made as follows, failing which, the unexecuted portion of the order will be cancelled and orders placed elsewhere and the earnest money deposited by the successful competitor forfeited as penalty for the non-execution of the order in full.

1. Hundred tins of kerosene oil within a week from the date of order placed with the successful competitor.

2. Seventy tins of kerosene oil on the first day of every succeeding month for nine months.

7. The name of the successful competitor whose tender has been accepted, will be posted on the "notice board" of the undersigned's office in the usual course and no enquiries regarding the acceptance or rejection of any tender will receive attention.

8. The successful competitor will be required to execute an agreement bond as per rules.

9. The mark or brand of the oil and its flashing point that each tenderer wishes to supply should also be stated distinctly.